Exam   :   **156-835**

Title   :   Check Point Certified
Maestro Expert

https://www.passcert.com/156-835.html

1.What is the purpose of Management ports located on the Rear Panel of the Orchestrator MHO-140?
A. Reserved for internal purposes. Not in use.
B. Out-of-band interfaces for access to Orchestrator itself.
C. 1Gbps connectivity for Security Groups.
D. Additional ports used as uplinks.
Answer: B

2.What is a Security Group?
A. Logical group of computer and network resources
B. Group of security administrators
C. Group of security gateways
D. Group of appliances with enabled NGTX software blades
Answer: C

3.Orchestrator should be defined in SmartConsole as:
A. Orchestrator is not defined in SmartConsole
B. Check Point host
C. Security Gateway
D. Host
Answer: A

4.What kinds of transceivers are supported on Orchestrator MHO-170?
A. QSFP. QSFP28
B. SFP. SFP+. SFP28
C. SFP+, SFP28. QSFP
D. SFP. QSFP, QSFP28
Answer: A

5.What does the lldpctl command do?
A. Show all devices discovered by LLDP protocol on downlink ports
B. Discover orchestrators
C. Show all devices discovered by LLDP protocol on uplink ports
D. Show all devices discovered by LLDP protocol on all ports
Answer: D

6.One single Appliance supports 1M concurrent connections.
How many concurrent connections will support Security Group of 2 Appliances?
A. 2M
B. 500K
C. 4M
D. 1M
Answer: A
Explanation:
One single Appliance supports 1M concurrent connections, so a Security Group of 2 Appliances will

support 2M concurrent connections.

How to troubleshoot Gaia Portal (WebUI)

https://supportcenter.checkpoint.com/supportcenter/portal?eventSubmit_doGoviewsolutiondetails=&solutionid=sk91380

VSX R81 Administration Guide

https://downloads.checkpoint.com/dc/download.htm?ID=103853

List of All Resolved Issues and New Features

https://sc1.checkpoint.com/documents/Jumbo_HFA/R81.10/R81.10/R81.10-List-of-all-Resolved-Issues.htm

7.What cannot be learned from the output ofasg monitorcommand?

A. Appliances cluster status

B. Port status

C. Uptime

D. D.Security Policy status

Answer: B

8.What command should be used for collecting diagnostic information about the orchestrator?

A. cpinfo

B. orch_info

C. cpview

D. asg pert -v

Answer: B

9.What is a downlink interface used for?

A. To connect Orchestrators to customer's infrastructure

B. To connect appliances to customer's infrastructure

C. To connect appliances to Orchestrators

D. To connect in between Orchestrators

Answer: C

10.Splitter cannot be used _____.

A. To connect single port on orchestrator to multiple Appliances

B. To connect single port on Appliance to multiple ports on the orchestrator

C. To connect single port on orchestrator to the same Appliance

D. To connect single port on orchestrator to multiple port on external switch

Answer: B